



5000 sq.ft./gallon

# BETCO EXPRESS®



## Fast Drying - Fast Curing Floor Finish • Max-Cure™ Technology

Betco Express® floor finish utilizes highly durable internally cross-linked polymers specially blended to minimize drying and cure times. Formulated with Max-Cure Technology™, each coat of finish dries and can be recoated in as little as 10 - 15 minutes. Betco Express® is perfect for use in applications where minimal down time is crucial such as 24/7 retail and health-care environments. The fast curing properties make this finish more suitable than conventional finishes in applications where high humidity or other conditions that may affect dry time exist. This product is designed to be applied in thin even coats for maximum performance.



### Uses

- Resilient tile

### Maintenance

- Moderate burnishing
- Low/High speed compatible

### Features

- Fast drying and curing allows rapid recoating.\*
- Coats dry in 10-15 minutes.\*
- Apply up to 6 coats in one hour.\*
- Up to 5,000 sq. ft. per gallon coverage.
- Can be used through Betco QUICKCOAT® II Applicator System for enhanced productivity.
- Can accept immediate airflow to accelerate dry time.
- Reduced down time, floors are back into service faster.
- Can be burnished between coats if desired for enhanced durability and gloss.
- Self sealing.
- Optically energized with XBF

\* When applied per label directions.

### Properties

Color (dried).....	Crystal clear
Color (liquid) .....	White
Coverage.....	5000 sq. ft./gallon
Dry time.....	10 - 15 minutes
Fragrance.....	Mild
Freeze/thaw stability .....	3 cycles
Gloss (ASTM D1455) .....	One coat 80 - 85 Two coats 90 - 95
Heel mark resistance .....	Very Good
Leveling.....	Excellent
pH.....	8.1 - 8.9
Powdering resistance .....	Excellent
Recoat .....	Excellent
Specific gravity .....	1.026
Free styrene content.....	0.0
Shelf life.....	1 year

Utilizes Betco's XBF technology for added brightness and extended durability.

### Directions For Use

Read the entire label before using this product.

**RESTORATIVE MAINTENANCE:** Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before applying finish. Rinse with clean water if necessary. Apply finish in even, THIN coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 10-15 minutes. This is a self sealing finish, however if tile is old, worn or porous a sealer can be used.

**ROUTINE MAINTENANCE:** Sweep large debris and dust mop regularly (use only water-based dust mop treatments). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish as desired. The use of a cleaner/restorer is recommended to condition the floor to extend the time between top scrubbing and recoating.

**INTERIM MAINTENANCE:** Sweep large debris and dust mop floor. Top scrub the floor using a top scrub cleaner and recommended floor pad to remove soiled layers of finish. Floor Surface must be clean, dry and free of residue before applying finish. Apply finish as directed above. **NOTE: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.**

### Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains emulsifiers. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician.

### Available In

- Case/4 - 1 Gallon (3.78 L): Item #65804-00
- Pail/5 Gallon (18.9 L): Item #65805-00
- Drum/55 Gallon (208 L): Item #65855-00
- Box/2-1.125 Gallon Bags (4.25 L): Item #65859-00 (QUICKCOAT® II)

Literature Item #65892-92

