



2,000 sq. ft./gallon

# BETSTONE® PENETRATING SEALER



## Natural Look • Stain Resistant • Penetrating Sealer

This water-base sealer deeply penetrates and saturates the pores of most hard surface stones for maximum protection. It bonds to the stone forming a barrier which resists staining yet allows the stone to breathe and release moisture vapors. This penetrating sealer is not a coating so it maintains the natural beauty of the existing stone.

### Uses

- Brick
- Ceramic tile
- Marble
- Non-sanded grout
- Porcelain tile
- Quarry tile
- Slate
- Terrazzo
- Sand stone
- Limestone
- Concrete
- Sanded grout
- Quartz
- Travertine

### Benefits

- Stain protection from oil-based, water-based and environmental particles.
- Retains original stone appearance.
- Easy to apply - spray or mop.
- Seals and protects grouting.
- Prevents damage from salts.
- Out performs silicone based sealers

### Properties

Color (dried) .....	Crystal Clear
Color (liquid) .....	Clear Amber
Coverage .....	2,000 sq.ft./gallon
Drying Time .....	8 hours
Fragrance .....	Mild
Leveling .....	Excellent
pH .....	7.5 - 9.5
Specific gravity .....	1.001
Shelf life .....	1 year

Authorized Betco Distributor



### Directions For Use

Read the entire label before using this product.

All tile and stone must be cemented and grouted following cure times per manufactures directions prior to application of this penetrating sealer. APPLICATION: All finishes or coatings must be removed prior to application. Surfaces must be cleaned with a mild detergent and rinsed with clean water. Allow surface to dry thoroughly prior to sealing. Apply the penetrating sealer with a clean synthetic finish mop or spray applicator. Apply liberally making sure all surfaces and grouting is thoroughly saturated. Allow the sealer to stand on the surface for no more than 5 minutes (not allowing to completely dry). Remove excess with a clean towel or use a 175 rpm machine with a carpet bonnet. If hazing occurs, lightly apply more sealer and immediately dry with a towel. A floor may accept traffic after 8 hours and full protection is obtained after 72 hours. For maximum protection, refrain from wet mopping or use of an auto scrubber with any detergents for 72 hours. After the first coat is applied, a second coat may be applied if the stone is very porous. Reapply after 3 - 6 months depending on foot traffic and cleaning frequency. Performance of the sealer may be affected by strong acidic, highly alkaline base cleaners or oxidizers.

### Safety

Keep out of reach of children. For institutional and commercial use only. WARNING: COMBUSTIBLE. Harmful if swallowed. Harmful if inhaled. FIRST AID: IF ON SKIN OR ON CLOTHING: Immediately remove contaminated clothing. Wash skin with soap and water. If irritation persists contact a physician. IF INHALED: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult oxygen may be administered by qualified personnel. Seek Medical attention. IF SWALLOWED: Seek IMMEDIATE medical attention, and show container or label. Induce vomiting only upon the advice of qualified medical personnel.

### Available In

Case/4 - 1 Gallon (3.78 L): Item #66904-00

Literature Item #66992-92

C1060 - Floor Care - Stone Flooring

02.08



The Cleaning Edge™